

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 236 863 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
04.09.2002 Bulletin 2002/36

(51) Int Cl.7: **E21B 43/26**(21) Application number: **02251171.1**(22) Date of filing: **20.02.2002**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Taylor, Robert S.**
Alberta, Canada T4P 3S9 (US)
• **Funkhouser, Gary P.**
Duncan, Oklahoma 73533 (US)


(30) Priority: **23.02.2001 US 792109**

(74) Representative: **Wain, Christopher Paul et al**
A.A. Thornton & Co.
235 High Holborn
London WC1V 7LE (GB)

(71) Applicant: **Halliburton Energy Services, Inc.**
Duncan, Oklahoma 73536 (US)

(54) Gelled hydrocarbon fluids for treating subterranean formations

(57) A hydrocarbon fracturing fluid for fracturing a subterranean formation containing a gelled liquid hydrocarbon made by adding a phosphonic acid ester having the formula:



where R is an alkyl group having from 8 to 24 carbon atoms.

A stoichiometric amount of a polyvalent metal source selected from ferric iron salts and aluminium compounds is also added. Water and an amount of a delayed gel breaker effective to break the gelled liquid hydrocarbon fracturing fluid is added to the hydrocarbon gelled liquid.

BEST AVAILABLE COPY

BEST AVAILABLE COPY

EP 1 236 863 A1

Description

[0001] This invention relates to hydrocarbon liquid gelling agents, to gelled liquid hydrocarbon fluids, and to methods of their use.

[0002] High viscosity gelled hydrocarbon liquids have heretofore been utilized in treating subterranean formations penetrated by well bores, e.g. hydraulic fracturing stimulation treatments. In such treatments, a high viscosity gelled liquid hydrocarbon fracturing fluid having particulate proppant material, e.g. sand, suspended therein is pumped through a well bore into a subterranean formation to be stimulated, at a rate and pressure such that one or more fractures are formed and extended in the formation. The suspended proppant material is deposited in the fractures when the gelled hydrocarbon fracturing fluid is broken and returned to the surface. The proppant material functions to prevent the formed fractures from closing whereby conductive channels remain through which produced fluids can readily flow to the well bore.


[0003] Polyvalent metal salts of orthophosphoric acid esters have heretofore been utilized as gelling agents for forming high viscosity gelled liquid hydrocarbon fracturing fluids. Such gelled liquid hydrocarbon fracturing fluids have included fracture proppant material and delayed breakers for causing the fracturing fluids to break into relatively thin fluids whereby the proppant material is deposited in formed fractures and the fracturing fluid is produced back. Descriptions of such heretofore utilized high viscosity gelled liquid hydrocarbon fracturing fluids and methods of their use are set forth in US patent no. 4,622,155 and US patent no. 5,846,915. The gelled liquid hydrocarbon fracturing fluids described in the above patents utilize ferric iron or aluminium polyvalent metal salts of phosphoric acid esters as gelling agents and delayed breakers such as hard burned magnesium oxide which is slowly soluble in water.

[0004] While the heretofore utilized high viscosity gelled liquid hydrocarbon fracturing fluids and methods have been used successfully for forming fractures in subterranean formations, problems have been encountered as a result of the use of the gelling agent, i.e. the polyvalent metal salt of a phosphoric acid ester. That is, in recent years plugging of refinery towers which process oil produced from formations fractured with gelled liquid hydrocarbon fracturing fluids has caused many expensive, unplanned shut-downs. The plugging material is high in phosphorus and has been attributed to the phosphate esters used as gelling agents. The phosphate esters contribute volatile phosphorus which condenses on distillation tower trays, causing plugging. The volatile phosphorus may also carry over the tops of the distillation towers causing contamination of the hydrocarbon products produced.

[0005] Thus, there are needs for improved methods of using and preparing gelled liquid hydrocarbons which upon breaking and being refined substantially reduce volatile phosphorus in distillation towers, improved liquid hydrocarbon gelling agents and improved gelled liquid hydrocarbon compositions. More specifically, in fracturing oil producing subterranean formations in areas where volatile phosphorus is a problem in refineries, there is a need to reduce the production of volatile phosphorus in the refineries to levels where the above described unscheduled refinery shut downs are not required without compromising CO₂ compatibility with the gelled oil fracturing fluids used. Concentrations of CO₂ as high as 40-50% are commonly used in gelled oil fracturing fluids which form miscible mixtures with the fluids. The presence of the CO₂ enhances fluid recovery, minimizes the amount of oil based fracturing fluid which must be recovered, and reduces costs in areas where CO₂ is less expensive than the oil based fracturing fluid.

[0006] We have now devised some improved liquid hydrocarbon gelling agents whereby many of the disadvantages in the prior art are mitigated or overcome.

[0007] In one aspect, the invention provides a hydrocarbon liquid gelling agent comprising a ferric iron or aluminium polyvalent metal salt of a phosphonic acid ester, said phosphonic acid ester having the formula




wherein R is an alkyl group having from about 8 to about 24 carbon atoms and R' is an alkyl group having from about 1 to about 4 carbon atoms.

[0008] The invention further provides a gelled liquid hydrocarbon fluid composition comprising a hydrocarbon liquid, a gelling agent comprised of a ferric iron or aluminium polyvalent metal salt of a phosphonic acid ester as defined above, water and an amount of a delayed gel breaker effective to break the gelled hydrocarbon fluid. The phosphonic acid ester utilized in the gelling agent minimizes volatile phosphorus in refinery distillation towers.

[0009] Fluid compositions of the invention which contain a proppant are useful as fracturing fluids.

[0010] The gelled liquid hydrocarbons of the invention are made by adding a phosphonic acid ester having the formula




where R is an alkyl group having from about 8 to about 24 carbon atoms and R' is an alkyl group having from about 1 to about 4 carbon atoms, and preferably, at least a stoichiometric amount of a polyvalent metal source selected from ferric iron salts and aluminium compounds, to a hydrocarbon liquid. The polyvalent metal source reacts with the phosphonic acid ester to form a ferric iron or aluminium polyvalent metal salt thereof. Water and an amount of a delayed gel breaker effective to break the gelled liquid hydrocarbon fracturing fluid is also added to the hydrocarbon liquid.

[0011] The present invention also provides a method of treating subterranean formations penetrated by well bores, with gelled liquid hydrocarbon fluids. For example, the gelled liquid hydrocarbon fluids are suitable for use in fracturing treatments carried out in subterranean formations whereby the production of hydrocarbons from the subterranean formations is stimulated. In accordance with the present invention, a fracturing fluid comprised of a gelled liquid hydrocarbon or mixture of hydrocarbons containing a proppant material and a delayed gel breaker is pumped through a well bore into a subterranean formation to be stimulated. The fracturing fluid is pumped at a rate and pressure such that one or more fractures are formed and extended in the subterranean formation. The proppant material which is suspended in the fracturing fluid is deposited in the fractures when the gel is broken and returned to the surface. The proppant material remains in the fractures and functions to prevent the fractures from closing whereby conductive channels are formed through which produced fluids can readily flow from the subterranean formation into the well bore.

[0012] As mentioned above, gelled liquid hydrocarbon fracturing fluids have heretofore been formed with a gelling agent comprised of a ferric iron or aluminum polyvalent metal salt of a phosphoric acid ester. The phosphoric acid ester suffers from the problem that it decomposes in refinery distillation towers to form volatile phosphorus which condenses on the trays of the distillation towers and causes plugging. Also, the phosphoric acid ester may itself be volatile, dependent upon its molecular weight. By the present invention, improved methods and compositions for fracturing subterranean formations with gelled liquid hydrocarbon fracturing fluids are provided wherein the gelling agent utilized is a ferric iron or aluminum polyvalent metal salt of a phosphonic acid ester. Unlike the phosphoric acid esters utilized heretofore, the phosphonic acid esters of the present invention have much higher thermal stability and consequently do not as readily decompose or disassociate in refining towers.

[0013] Thus, the improved methods of fracturing subterranean formations of the present invention are basically comprised of the following steps. A gelled liquid hydrocarbon fracturing fluid is prepared comprised of a hydrocarbon liquid, a ferric iron or aluminum polyvalent metal salt of a phosphonic acid ester, a proppant material, water and an amount of a delayed gel breaker effective to break the gelled liquid hydrocarbon fracturing fluid. The phosphonic acid ester has the formula



wherein R is an alkyl group having from about 8 to about 24 carbon atoms and R' is an alkyl group having from about 1 to about 4 carbon atoms. After the gelled liquid hydrocarbon fracturing fluid is prepared, the subterranean formation to be fractured is contacted with the fracturing fluid under conditions effective to create at least one fracture in the subterranean formation.


[0014] The hydrocarbon liquid utilized to form the gelled liquid hydrocarbon fracturing fluid can be any of the various previously used hydrocarbon liquids including, but not limited to, olefins, kerosene, diesel oil, gas oil (also known as gas condensate), fuel oil, other petroleum distillates, and certain mixtures of crude oil. Liquid hydrocarbon fracturing

fluids which are specifically designed for use with CO₂ are generally preferred. Such a liquid hydrocarbon fracturing fluid is commercially available from the Trysol Corporation of Sundre, Alberta, Canada under the trade name "FRAC-SOL™."

[0015] As mentioned above, the gelling agent utilized for gelling the hydrocarbon liquid whereby it has a high viscosity sufficient to carry suspended proppant material and produce fractures in a subterranean formation is a ferric iron or aluminum polyvalent metal salt of a phosphonic acid ester having the formula set forth above. The polyvalent metal salt of the phosphonic acid ester is preferably produced at the well site by adding the phosphonic acid ester, and preferably, at least a stoichiometric amount of a polyvalent metal salt (preferably a ferric iron salt or an aluminum compound). In addition, if water is not already contained in the hydrocarbon liquid or added thereto as a component in a cross-linker solution or the like, water is added to the hydrocarbon liquid in an amount, for example, of about 0.05% or greater by weight of the hydrocarbon liquid. The presence of the water allows slowly water soluble or encapsulated breakers to be dissolved or released. See, for example, Smith et al. U.S. Patent No. 5,846,915 issued on December 8, 1995 which is incorporated herein by reference.

[0016] When a ferric iron salt is utilized to form the gelling agent, it is preferably selected from ferric sulfate or ferric chloride with ferric sulfate being preferred. The ferric iron salt is typically mixed with amines, surfactants and water to form a liquid cross-linking solution. An example of a commercially available ferric iron cross-linking solution is "EA-3™" cross-linking solution sold by Ethox Chemicals, Inc. of Greenville, South Carolina. When an aluminum compound is utilized, it is preferably selected from aluminum chloride or aluminum isopropoxide, with aluminum chloride being the most preferred. The polyvalent metal compound utilized reacts with the phosphonic acid ester to form the hydrocarbon liquid gelling agent of this invention which gels the hydrocarbon liquid. The phosphonic acid ester is added to the hydrocarbon liquid along with the polyvalent metal source to form the gelling agent in the hydrocarbon liquid in an amount in the range of from about 0.1% to about 2.5% by weight of the hydrocarbon liquid.

[0017] As mentioned above, the phosphonic acid ester which can be utilized to form the hydrocarbon liquid gelling agent of this invention has the formula



wherein R is an alkyl group having from about 8 to about 24 carbon atoms and R' is an alkyl group having from about 1 to about 4 carbon atoms. Techniques which can be utilized for the preparation of the phosphonic acid esters useful in accordance with this invention are, for example, described in U.S. Patent No. 3,798,162 issued to Dickert, Jr. on March 19, 1974 which is incorporated herein by reference.

[0018] Proppant materials which can be utilized in the fracturing fluids of this invention are well known in the art. For example, proppant materials such as graded sand, resin coated sand, sintered bauxite, various particulate ceramic materials, glass beads and the like can be utilized. The particular size of the proppant material employed depends on the particular formation being fractured and other variables. Generally, the proppant particle sizes are in the range of from about 2 to about 200 mesh on the U.S. Sieve Series scale.


[0019] A variety of delayed gel breakers can be utilized in accordance with the present invention to cause the gelled liquid hydrocarbon fracturing fluid to revert to a thin fluid that is produced back after fractures are formed in a subterranean formation. The gel breakers can be materials which are slowly soluble in water which, as mentioned above, is combined with or otherwise present in the hydrocarbon liquid. The breaking of the gel does not take place until the slowly soluble breakers are dissolved in the water. Examples of such slowly soluble breakers are given in U.S. Patent No. 5,846,915 issued to Smith et al. on December 8, 1998 which is incorporated herein by reference. As indicated in Patent No. 5,846,915, hard burned magnesium oxide having a particle size which will pass through a 200 mesh Tyler screen is preferred. The hard burned magnesium oxide and other similar breakers are not immediately present for breaking the gel due to their slowly soluble nature. Other breakers such as alkali metal carbonates, alkali metal bicarbonates, alkali metal acetates, other alkaline earth metal oxides, alkali metal hydroxides, amines, weak acids and the like can be encapsulated with slowly water soluble or other similar encapsulating materials. Such materials are well known to those skilled in the art and function to delay the breaking of the gelled hydrocarbon liquid for a required period of time. Examples of water soluble and other similar encapsulating materials which can be utilized include, but are not limited to, porous solid materials such as precipitated silica, elastomers, polyvinylidene chloride (PVDC), nylon, waxes, polyurethanes, cross-linked partially hydrolyzed acrylics and the like. Of the slowly soluble or encapsulated breakers mentioned, hard burned magnesium oxide which is commercially available from Clearwater Inc. of Pittsburgh, Pennsylvania is preferred for use in accordance with the present invention. When an alkaline breaker is utilized, e.g., mag-

nesium oxide, the acid group of the phosphonic acid ester in the gelling agent is neutralized which initially increases the viscosity of the gelled hydrocarbon liquid after which the gel is broken.

[0020] Another type of breaker which can be utilized when the gelling agent is a ferric iron polyvalent metal salt of a phosphonic acid ester of this invention, or a ferric iron polyvalent metal salt of the heretofore used phosphoric acid ester, is a reducing agent that reduces ferric iron to ferrous iron. Since only ferric iron is capable of forming a viscous coordination complex with a phosphonic acid ester or a phosphoric acid ester, the complex can be disassociated by reducing the ferric iron to the ferrous state. The disassociation causes the gelled hydrocarbon liquid to break. Examples of reducing agents which can be utilized include, but are not limited to, stannous chloride, thioglycolic acid (2-mercaptoacetic acid), hydrazine sulfate, sodium diethyldithiocarbamate, sodium dimethyldithiocarbamate, sodium hypophosphite, potassium iodide, hydroxylamine hydrochloride, thioglycol (2-mercaptoethanol), ascorbic acid, sodium thiosulfate, sodium dithionite and sodium sulfite. Of these, the preferred reducing agents for use at a temperature of about 90°C are stannous chloride, thioglycolic acid, hydrazine sulfate, sodium diethyldithiocarbamate and sodium dimethyldithiocarbamate. The most preferred reducing agent is thioglycolic acid which may be delayed by salt formation or encapsulation. As mentioned above in connection with other breakers that can be used, the reducing agent utilized can also be delayed by encapsulating it with a slowly water soluble or other similar encapsulating material.

[0021] The gel breaker utilized in a water-containing gelled liquid hydrocarbon fracturing fluid of this invention is generally present therein in an amount in the range of from about 0.01% to about 3% by weight of the hydrocarbon liquid, more preferably in an amount in the range of from about 0.05% to about 1%.


[0022] A preferred method of fracturing a subterranean formation in accordance with the present invention is comprised of the steps of: (a) preparing a gelled liquid hydrocarbon fracturing fluid comprised of a hydrocarbon liquid, a ferric iron or aluminum polyvalent metal salt of a phosphonic acid ester, the phosphonic acid ester having the formula



wherein R is an alkyl group having from about 8 to about 24 carbon atoms and R' is an alkyl group having from about 1 to about 4 carbon atoms, a proppant material, water and an amount of a delayed gel breaker effective to break the gelled hydrocarbon fracturing fluid; and (b) contacting the subterranean formation with the gelled hydrocarbon fracturing fluid under conditions effective to create at least one fracture in the subterranean formation.

[0023] The ferric iron or aluminum polyvalent metal salt of the phosphonic acid ester is present in the fracturing fluid in an amount in the range of from about 0.1% to about 2.5% by weight of the hydrocarbon liquid in the fracturing fluid, more preferably in an amount in the range of from about 0.2% to about 1%. The proppant material is present in the fracturing fluid in an amount in the range of from about 1 to about 14 pounds of proppant material per gallon of hydrocarbon liquid in the fracturing fluid. As mentioned, water is added to or otherwise contained in the hydrocarbon liquid so that the delayed gel breaker utilized is dissolved in the water. The delayed gel breaker is present in the fracturing fluid in an amount in the range of from about 0.01% to about 3% by weight of the hydrocarbon liquid in the fracturing fluid, more preferably in an amount in the range of from about 0.05% to about 1%.

[0024] A preferred method of preparing a gelled liquid hydrocarbon fluid of this invention is comprised of adding a phosphonic acid ester to a hydrocarbon liquid, the phosphonic acid ester having the formula




wherein R is an alkyl group having from about 8 to about 24 carbon atoms and R' is an alkyl group having from about 1 to about 4 carbon atoms, at least a stoichiometric amount of a polyvalent metal source selected from ferric iron salts and aluminum compounds which reacts with the phosphonic acid ester to form a ferric iron or aluminum polyvalent metal salt thereof, water and an amount of a delayed gel breaker effective to break the gelled hydrocarbon fracturing fluid.

[0025] The ferric iron or aluminum polyvalent metal salt of the phosphonic acid ester formed in the hydrocarbon liquid is present therein in an amount in the range of from about 0.1% to about 2.5% by weight of the hydrocarbon liquid,


more preferably in an amount in the range of from about 0.2% to about 1%. The delayed gel breaker utilized is present in the hydrocarbon liquid in an amount in the range of from about 0.01% to about 3% by weight of the hydrocarbon liquid, more preferably in an amount in the range of from about 0.05% to about 1%.

[0026] A preferred hydrocarbon liquid gelling agent of this invention is comprised of a ferric iron or aluminum polyvalent metal salt of a phosphonic acid ester, the phosphonic acid ester having the formula




wherein R is an alkyl group having from about 8 to about 24 carbon atoms and R' is an alkyl group having from about 1 to about 4 carbon atoms.

[0027] A more preferred hydrocarbon liquid gelling agent is comprised of a ferric iron polyvalent metal salt of a phosphonic acid ester, the ester having the formula



wherein R is an alkyl group having from about 14 to about 24 carbon atoms and R' is a methyl group.

[0028] A preferred gelled liquid hydrocarbon composition of this invention is comprised of: a hydrocarbon liquid; a gelling agent comprising a polyvalent metal salt of a phosphonic acid ester produced from a phosphonic acid ester and a ferric iron salt or an aluminum compound, the phosphonic acid ester having the formula



wherein R is an alkyl group having from about 14 to about 24 carbon atoms and R' is a methyl group, water and a delayed gel breaker present in an amount effective to break the gel formed by the gelling agent and the hydrocarbon liquid.

[0029] As mentioned above, the delayed gel breaker can be alkaline earth metal oxides including hard burned magnesium oxide, alkali metal carbonates, alkali metal bicarbonates, alkali metal acetates, alkali metal hydroxides, amines and weak acids which are slowly water soluble or are encapsulated with a slowly water soluble or other similar encapsulating material. The delayed gel breaker can also be a reducing agent that reduces ferric iron to ferrous iron encapsulated with a slowly water soluble or other similar encapsulating material. The delayed gel breaker is present in the gelled hydrocarbon liquid in an amount in the range of from about 0.01% to about 3% by weight of the hydrocarbon liquid, more preferably in an amount in the range of from about 0.05% to about 1%.

[0030] As will be understood by those skilled in the art, the use of the improved liquid hydrocarbon gelling agents and gelled liquid hydrocarbon compositions is not limited to fracturing subterranean formations. For example, the gelled liquid hydrocarbon compositions can be used for forming gravel packs in well bores, in pipeline pigging operations and in other operations where a gelled hydrocarbon liquid which subsequently breaks into a thin fluid is utilized.

[0031] In order to further illustrate the methods and composition of the present invention, the following examples are given.

Example 1

[0032] A number of monoesters of alkylphosphonic acids were prepared in the laboratory as follows: solid dodecylphosphonic acid monomethyl ester, solid tetradecylphosphonic acid monomethyl ester, solid hexadecylphosphonic

acid monomethyl ester, solid octadecylphosphonic acid monomethyl ester, solid C₂₀₋₂₄ phosphonic acid monomethyl ester, solid octadecylphosphonic acid monobutyl ester, liquid octylphosphonic acid monomethyl ester and liquid decylphosphonic acid monomethyl ester.

[0033] The following laboratory procedure was utilized in the preparation of the above listed esters. Alkylphosphonic acid dimethyl (or dibutyl) esters were first prepared by charging a 250 milliliter three necked round bottom flask with 0.2 mole of 1-alkene and 0.5 mole of dimethyl or dibutyl phosphite. The flask was fitted with a reflux condenser, thermometer, temperature controller, septum stopper and nitrogen purge. The mixture was magnetically stirred and heated to 150°C or the boiling point of the 1-alkene, whichever was lower. 2.5 milliliters of t-butyl peroxide was slowly added with a syringe over the course of 1 hour. The mixture was heated at 150°C for another 1.5 hours. The excess dialkyl phosphite was removed using vacuum distillation.

[0034] The following laboratory procedure was utilized in the preparation of monomethyl (or monobutyl) esters that are liquids at room temperature. That is, alkylphosphonic acid monomethyl (or monobutyl) esters were prepared using the alkylphosphonic acid dimethyl (or dibutyl) esters prepared in accordance with the above described procedure as follows. 0.045 mole of alkylphosphonic acid dimethyl (or dibutyl) ester was charged to a 100 milliliter round bottom flask. A solution of 1.9 grams (0.048 mole) of sodium hydroxide in 38 milliliters of methanol was added to the flask and the flask was fitted with a reflux condenser. The mixture was stirred magnetically and heated to reflux for 3 hours. 10 milliliters of water and 50 milliliters of hexane were added and the resulting mixture was shaken. The phases were separated and the hexane layer containing the unreacted dimethyl (or dibutyl) ester was discarded. The aqueous layer was washed twice with 20 milliliter portions of hexane and the hexane layer was discarded. 3.6 milliliters of 38% hydrochloric acid (0.045 mole) was added to the aqueous phase followed by 40 milliliters of water. The mixture was extracted 3 times with 20 milliliter portions of hexane. The combined organic fractions were washed with water and dried over anhydrous magnesium sulfate. The solvent was removed using a rotary evaporator. The alkylphosphonic acid monomethyl (or monobutyl) esters produced were liquids at room temperature.

[0035] Alkylphosphonic acid monoesters which are solids at room temperature were also prepared. These were the C₁₂ to C₂₄ alkyl phosphonic acid mono methyl esters. The following laboratory procedure was utilized. A 100 milliliters round bottom flask was charged with 0.05 mole of alkylphosphonic acid dimethyl ester and the flask was warmed to melt the solid. A solution of 2.5 g (0.063 mole) of sodium hydroxide in 38 milliliters of methanol was added and the flask was fitted with a reflux condenser. The mixture was stirred magnetically and heated to reflux for 3 hours. The flask was cooled and 5 milliliters 38% hydrochloric acid (0.062 mole) was added, followed by the addition of 125 milliliters of water. The slurry was extracted into hexane. The hexane solution was washed with water, dried over anhydrous magnesium sulfate, and concentrated on a rotary evaporator. The product was allowed to recrystallize, then it was collected on a büchner funnel, washed with hexane, and air dried.

Example 2

[0036] A commercially available octylphosphonic acid monomethyl ester was obtained which contained 55-65% octylphosphonic acid monomethyl ester, 20-30% octylphosphonic acid and 10-20% octylphosphonic acid dimethyl ester. 2 milliliters of the commercial octylphosphonic acid monomethyl ester and 2 milliliters of a ferric iron cross-linker commercially available from Clearwater Inc. of Pittsburgh, Pennsylvania under the trade designation "HGA-65™" were added to 200 milliliters of kerosene. Initial cross-linking was observed after 20 seconds of stirring with an overhead stirrer. A strong cross-linked gel was observed after 1 minute.

[0037] This test shows that the phosphonic acid ester does not have to be pure, i.e., it can contain portions of the phosphonic acid and the phosphonic acid dialkyl ester.

Example 3

[0038] 2 milliliters of the commercially available octylphosphonic acid monomethyl ester described in Example 2 were added to 200 milliliters of kerosene along with a ferric iron cross-linker composition. The ferric iron cross-linker composition was comprised of 240 grams of deionized water, 60 grams of ferric sulfate pentahydrate and 33.3 grams of triethanolamine.

[0039] Upon mixing, the cross-linking reaction was slower than that observed in Example 2, but good cross-linking was observed after 2 to 3 minutes.

Example 4

[0040] The commercially available octylphosphonic acid monomethyl ester described in Example 2 was added to No. 2 off-road diesel oil along with a commercially available ferric iron cross-linking composition obtained from Ethox Chemicals, Inc. of Greenville, S.C. sold under the trade designation "EA-3™" (see U.S. Patent No. 6,149,693 issued

to Geib on November 21, 2000). Three different mixtures were prepared having the quantities of components shown in Table I below. After mixing, each of the mixtures was placed in a Model 50 viscometer at 68°C and the viscosities of the mixtures were observed over time. The results of these tests are given in Table I below.

TABLE I

Viscosities Of Gelled Diesel Oil Using Commercially Available Gelling Agent Components At 68°C			
Time, minutes	Viscosity, cp. @ 170/sec		
	Mixture A ¹	Mixture B ²	Mixture C ³
30	297	169	197
60	243	172	210
90	218	187	212
120	205	209	204
150	193	217	199
180	184	218	193
210	175	218	188
240	167	217	184
270	158	216	182
300	152	217	-

¹Mixture A was comprised of 6 milliliters of commercially available Albright & Wilson "ITC™-996," octylphosphonic acid monomethyl ester per liter of diesel oil and 5 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

²Mixture B was comprised of 5 milliliters of commercially available Albright & Wilson "ITC™-996," octylphosphonic acid monomethyl ester per liter of diesel oil and 5 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

³Mixture C was comprised of 5 milliliters of commercially available Albright & Wilson "ITC™-996," octylphosphonic acid monomethyl ester per liter of diesel oil and 6 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

[0041] From Table I it can be seen that the commercially available octylphosphonic acid monomethyl ester and cross-linker produced rapid cross-linking and excellent viscosities.

Example 5

[0042] The procedure of Example 4 was repeated except that the octylphosphonic acid monomethyl ester was synthesized in accordance with the procedure set forth in Example 1 and the third mixture tested, i.e., mixture F, included magnesium oxide breaker. The results of these tests are given in Table II below.

TABLE II

Viscosities Of Gelled Diesel Oil Using Synthesized Octylphosphonic Acid Monomethyl Ester And Commercial Ferric Iron Cross-Linking Composition At 68°C			
Time, minutes	Viscosity, cp. @ 170/sec		
	Mixture D ¹	Mixture E ²	Mixture F ³
4	299	388	395
30	131	143	85
60	135	146	47
90	140	151	34
120	146	156	25
150	149	160	17
180	-	162	10
210	-	163	-
240	-	164	-

¹Mixture D was comprised of 5 milliliters of synthesized octylphosphonic acid monomethyl ester per liter of diesel oil and 5 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

²Mixture E was comprised of 5 milliliters of synthesized octylphosphonic acid monomethyl ester per liter of diesel oil and 6 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

³Mixture F was comprised of 5 milliliters of synthesized octylphosphonic acid monomethyl ester per liter of diesel oil, 5 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil and 1.2 grams magnesium oxide breaker per liter of diesel oil.

[0043] From Table II it can be seen that the synthesized octylphosphonic acid monomethyl ester produced excellent gels. In addition, mixture F including magnesium oxide gel breaker showed an increased viscosity as a result of neutralization of the phosphonic acid ester by the magnesium oxide breaker therein after which the gel was broken.

5 **Example 6**

[0044] The procedure of Example 4 was repeated except that the phosphonic acid ester used was synthesized hexadecylphosphonic acid monomethyl ester. The results of these tests are given in Table III set forth below.

10

15

20

25

30

35

40

45

50

55

TABLE III
Viscosities Of Gelled Diesel Oil Using Synthesized Hexadecylphosphonic Acid
Monomethyl Ester And Commercial Ferric Iron Cross-Linking Composition At 68°C

Time, minutes	Viscosity, cp. @ 170/sec							
	Mixture G ¹	Mixture H ²	Mixture I ³	Mixture J ⁴	Mixture K ⁵	Mixture L ⁶	Mixture M ⁷	Mixture N ⁸
3.5	36	121	70	162	107	179	235	292
30	145	199	190	183	165	177	175	186
60	171	176	169	195	166	187	172	181
90	177	186	169	208	167	192	173	177
120	187	197	175	213	169	194	174	172
150	189	203	179	218	175	200	178	176
180	191	209	189	221	181	202	178	174
195	193	209	190	222	181	203	181	174

¹Mixture G was comprised of 0.02 M (6.4 g/L) synthesized hexadecylphosphonic acid monomethyl ester per liter of diesel oil and 4.0 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

²Mixture H was comprised of 0.02 M (6.4 g/L) synthesized hexadecylphosphonic acid monomethyl ester per liter of diesel oil and 5.0 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

³Mixture I was comprised of 0.02 M (6.4 g/L) synthesized hexadecylphosphonic acid monomethyl ester per liter of diesel oil and 5.5 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

⁴Mixture J was comprised of 0.02 M (6.4 g/L) synthesized hexadecylphosphonic acid monomethyl ester per liter of diesel oil and 6.0 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

⁵Mixture K was comprised of 0.02 M (6.4 g/L) synthesized hexadecylphosphonic acid monomethyl ester per liter of diesel oil and 6.5 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

⁶Mixture L was comprised of 0.02 M (6.4 g/L) synthesized hexadecylphosphonic acid monomethyl ester per liter of diesel oil and 7.0 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

⁷Mixture M was comprised of 0.02 M (6.4 g/L) synthesized hexadecylphosphonic acid monomethyl ester per liter of diesel oil and 9.0 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

⁸Mixture N was comprised of 0.02 M (6.4 g/L) synthesized hexadecylphosphonic acid monomethyl ester per liter of diesel oil and 11.0 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

[0045] From Table III it can be seen that synthesized hexadecylphosphonic acid monomethyl ester and the ferric iron cross-linker utilized form excellent gels in diesel oil at 68°C.

Example 7

[0046] The test procedure of Example 4 was repeated except that synthesized octadecylphosphonic acid monomethyl ester was utilized, the temperature of the gelled diesel oil was increased over time and two of the four gelled mixtures tested contained a magnesium oxide breaker. The results of these tests are given in Table IV below.

TABLE IV
Viscosities Of Gelled Diesel Oil Using
Synthesized Octadecylphosphonic Acid Monomethyl Ester And
Commercial Ferric Iron Cross-Linking Composition At Various Temperatures

Time, minutes	Mixture O ¹		Mixture P ²		Mixture Q ³		Mixture R ⁴	
	Temp., °C	Viscosity, cp. @ 170/sec	Temp., °C	Viscosity, cp. @ 170/sec	Temp., °C	Viscosity, cp. @ 170/sec	Temp., °C	Viscosity, cp. @ 170/sec
0	33	236	32	165	26	210	27	260
30	66	243	66	200	67	245	55	295
60	67	247	68	220	68	250	88	320
90	67	247	68	222	68	253	117	355
120	67	247	68	227	68	255	141	375
150	86	254	85	265	86	280	145	390
180	132	44	129	60	131	45	152	310
210	145	37	145	42	145	35	162	150
240	146	36	146	42	146	32	173	27
270	-	-	-	-	-	-	174	16
300	-	-	-	-	-	-	183	15
330	-	-	-	-	-	-	193	14

¹Mixture O was comprised of 0.02 M (7 g/L) synthesized octadecylphosphonic acid monomethyl ester per liter of diesel oil and 5 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

²Mixture P was comprised of 0.02 M (7 g/L) synthesized octadecylphosphonic acid monomethyl ester per liter of diesel oil, 5 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil and 0.24 grams of magnesium oxide breaker per liter of diesel oil.

³Mixture Q was comprised of 0.02 M (7 g/L) synthesized octadecylphosphonic acid monomethyl ester per liter of diesel oil and 6 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil.

⁴Mixture R was comprised of 0.04 M (14 g/L) synthesized octadecylphosphonic acid monomethyl ester per liter of diesel oil, 12 milliliters of "ETHOX™ EA-3" ferric iron cross-linker composition per liter of diesel oil and 0.48 grams of magnesium oxide breaker per liter of diesel oil.

[0047] As can be seen from Table IV, synthesized octadecylphosphonic acid monomethyl ester and the ferric iron cross-linker utilized form excellent gels in diesel oil over a broad temperature range. Further, the magnesium oxide breaker neutralized the acid ester which increased the viscosity attained over a broad range of temperatures.

Example 8

[0048] The test procedure of Example 4 was repeated except that a Tempco Rheo-15 rheometer was utilized to measure apparent viscosities at various temperatures with fluids containing 40% CO₂ by volume. One of the test mixtures was formed with a #2 Off Road Diesel hydrocarbon fluid and another test mixture included magnesium oxide. The results of these tests are set forth in Table V below.

TABLE V

Viscosities Of Gelled Diesel Using Commercially Available Gelling Agent Components And 40% Carbon Dioxide By Volume At Various Temperatures						
Time, minutes	Mixture S ¹		Mixture T ²		Mixture U ³	
	Temp., °C	Viscosity, cp. @ 170/sec	Temp., °C	Viscosity, cp. @ 170/sec	Temp., °C	Viscosity, cp. @ 170/sec
0	10	120	7	120	7	100
10	66	155	52	195	60	295
20	85	115	66	205	63	330
30	85	95	68	195	66	340
40	85	85	71	190	68	345
50	85	85	74	175	71	350
60	85	85	77	165	72	350
70	-	-	82	145	74	340
80	-	-	85	130	77	335
90	-	-	88	110	79	320
100	-	-	91	90	85	315
110	-	-	93	80	88	300
120	-	-	96	65	90	285
130	-	-	99	45	91	265
140	-	-	102	35	93	240
150	-	-	104	20	96	210

¹Mixture S was comprised of 5 milliliters of commercially available Albright & Wilson "ITC™-966" octylphosphonic acid monomethyl ester per liter of #2 Off Road Diesel Fuel containing 40% by volume carbon dioxide and 5 milliliters of Ethox "EA-3™" ferric iron cross-linker composition per liter of #2 Off Road Diesel Fuel containing 40% by volume carbon dioxide.

²Mixture T was comprised of 7 milliliters of commercially available Albright & Wilson "ITC™-966" octylphosphonic acid monomethyl ester per liter of diesel oil containing 40% by volume carbon dioxide and 7 milliliters of Ethox "EA-3™" ferric iron cross-linker composition per liter of diesel oil containing 40% by volume carbon dioxide.

³Mixture U was comprised of 7 milliliters of commercially available Albright & Wilson "ITC™-966" octylphosphonic acid monomethyl ester per liter of #2 Off Road Diesel Fuel containing 40% by volume carbon dioxide, 7 milliliters of Ethox "EA-3™" ferric iron cross-linker composition per liter of #2 Off Road Diesel Fuel containing 40% by volume carbon dioxide and 0.240 grams of magnesium oxide breaker per liter of diesel oil containing 40% by volume carbon dioxide.

[0049] From Table V it can be seen that excellent gels were formed even though the gels contained 40% by volume carbon dioxide. Also, a significant increase in viscosity was realized when the gel included only enough magnesium oxide breaker to partially neutralize the octyl phosphonic acid monomethyl ester.

Example 9

[0050] Various synthesized phosphonic acid esters were added in various amounts to diesel oil or kerosene along with various amounts of ETHOX "EA-3™" ferric iron cross-linker compositions and the resulting gels were observed. The results of these tests are set forth in Table VI below.

TABLE VI
Observations Of Various Gels
Formed With Alkylphosphonic Acid
Monomethyl Esters And Commercial Cross-Linkers

Hydrocarbon Liquid Used	Ester	Ester Amount In Hydrocarbon Liquid	Cross-Linker	Cross-Linker Amount, ml/L of hydrocarbon liquid	Observations
Off-road Diesel	Octylphosphonic acid monomethyl ester	2.0 ml/L	Ethox "EA-3™"	2	weak elastic gel
Off-road Diesel	Octylphosphonic acid monomethyl ester	33.0 ml/L	Ethox "EA-3™"	3	weak lipping gel
Off-road Diesel	Octylphosphonic acid monomethyl ester	5.0 ml/L	Ethox "EA-3™"	5	strong lipping gel
Off-road Diesel	Decylphosphonic acid monomethyl ester	5.0 ml/L	Ethox "EA-3™"	10	weak elastic gel
Off-road Diesel	Decylphosphonic acid monomethyl ester	10.0 ml/L	Ethox "EA-3™"	5	lipping gel
Kerosene	Hexadecylphosphonic acid monomethyl ester	9.9 g/L	Ethox "EA-3™"	10	very strong lipping gel
Kerosene	Octadecylphosphonic acid monobutyl ester	8.0 g/L	Ethox "EA-3™"	6	very strong lipping gel
Kerosene	Octylphosphonic acid monomethyl ester ¹	10.0 ml/L	Aluminum compound ²	0.8	good lipping gel

¹Albert & Wilson "ITC-966™" ester

²Aluminum cross-linker commercially available from Halliburton Energy Services, Inc. of Duncan, Oklahoma.

Example 10

[0051] The procedure described in Example 4 was repeated except that magnesium oxide breaker was included in the three mixtures that were tested. In addition, one of the gels was produced utilizing a hydrocarbon liquid commercially available from Trisol Corp. of Sundre, Alberta, Canada under the trade name "FRACSOL™" to which was added 40% by total volume carbon dioxide. The results of the tests are given in VII below.

TABLE VII

Break Times Of Various Gels With Magnesium Oxide						
Time, minutes	Mixture V ¹		Mixture W ²		Mixture X ³	
	Temp., °C	Viscosity, cp. @ 170/sec	Temp., °C	Viscosity, cp. @ 170/sec	Temp., °C	Viscosity, cp. @ 170/sec
5	31	366	33	375	39	370
10	46	365	48	307	68	365
15	54	365	55	240	85	360
20	59	364	58	173	85	200
25	62	363	61	105	85	70
30	64	360	62	83	85	30
35	65	357	64	76	85	15
40	66	353	65	67	85	13
45	67	335	65	62	85	10
50	67	318	66	56	85	9
55	67	302	66	51	85	5
60	68	293	66	47	85	2
90	68	185	66	34		
120	68	97	67	25		
150	68	74	67	17		
180	68	67	67	11		
210	68	60				
240	68	54				
270	68	47				
300	68	35				
330	68	25				
360	68	18				
390	68	14				
420	68	12				

¹Mixture V was comprised of 5 milliliters of commercially available Albright & Wilson "ITC™-966" octylphosphonic acid monomethyl ester per liter of off-road diesel oil, 5 milliliters of Ethox "EA-3™" ferric iron cross-linker composition per liter of off-road diesel oil and 2.4 grams of magnesium oxide breaker per liter of off-road diesel oil. The off-road diesel oil contained water.

²Mixture W was comprised of 5 milliliters of synthesized octylphosphonic acid monomethyl ester per liter of off-road diesel oil, 5 milliliters of Ethox "EA-3™" ferric iron cross-linker composition per liter of off-road diesel oil and 1.2 grams of magnesium oxide breaker per liter of off-road diesel oil. The off-road diesel oil contained water.

³Mixture X was comprised of 7 milliliters of commercially available Albright & Wilson "ITC™-966" octylphosphonic acid monomethyl ester per liter of "FRACSOL™" hydrocarbon liquid mixed with 40% by volume carbon dioxide, 7 milliliters of Ethox "EA-3™" ferric iron cross-linker composition per liter of "FRACSOL™" hydrocarbon liquid mixed with 40% by volume carbon dioxide and 1.1 grams of magnesium oxide breaker per liter of "FRACSOL™" hydrocarbon liquid mixed with 40% by volume carbon dioxide. Mixture X also contained water.

[0052] From Table VII, it can be seen that complete progressive breaks were obtained by the presence of the magnesium oxide. The synthesized phosphonic acid ester required significantly less breaker and still showed a faster break rate than the commercial phosphonic acid ester. The gel containing 60% by volume "FRACSOL™" hydrocarbon liquid and 40% by volume carbon dioxide also achieved a progressive and complete break as a result of the presence of the magnesium oxide.

Example 11

[0053] Gelled hydrocarbon liquid test samples were prepared by combining 0.02M (6.4 g/L) of hexadecylphosphonic acid monomethyl ester and 5 milliliters of ethox "EA-3™" ferric iron cross-linker composition to 1 liter of off-road diesel oil. Various reducing agents for reducing ferric iron to ferrous iron and thereby breaking the gels were added to the test samples. Thereafter, the viscosities of the test samples over time were measured to determine the effectiveness of the reducing agents in breaking the gels. The results of these tests are given in Table VIII below.

TABLE VIII

Break Times Of Diesel Oil Gel ¹ Containing Various Reducing Agents @ 90°C					
Reducing Agent Used	Viscosity, cp. @ 170/sec At Time				
	0	2 hrs.	21 hrs.	45 hrs.	242 hrs.
Blank - No Reducing Agent	60	66	66	66	66
Stannous Chloride dihydrate	7	3	-	-	-
Thioglycolic Acid	45	3	-	-	-
Sodium Diethyldithiocarbamate	141	18	3	-	-
Sodium Dimethyldithiocarbamate	123	42	30	3	-
Hydrazine Sulfate	45	96	57	33	3
Hydroxylamine Hydrochloride	75	69	15	3	-

¹0.02M (0.64 wt%) hexadecyl phosphonic acid mono methyl ester per liter of off-road diesel oil, 5 milliliters of Ethox "EA-3™" ferric iron cross-linker composition per liter of off-road diesel oil and 0.01M reducing agent per liter of off-road diesel oil. [0.1 Molar for stannous chloride dihydrate = 22.56 g/L; 0.1 M for thioglycolic acid (mercaptoacetic acid) = 9.21 g/L; 0.1 M for sodium diethyldithiocarbamate = 22.53 g/L; 0.1 M for sodium dimethyldithiocarbamate = 14.32 g/L; 0.1 m hydroxylamine hydrochloride = 6.95 g/L] The off-road diesel oil gels contained water.

[0054] From Table VIII it can be seen that reducing agents comprised of stannous chloride, thioglycolic acid, sodium diethyldithiocarbamate, sodium dimethyldithiocarbamate and hydrazine sulfate can be utilized as efficient reducing agent breakers for the hydrocarbon gels of this invention, at 90°C.

[0055] Additional reducing agents were evaluated but found to be too weak with phosphonates gels, at 90°C. However, it is understood the additional reducing agents could be the preferred reducing agents at higher temperatures where a slower rate of reaction is required. The additional reducing agents include, but are not limited to, sodium hypophosphite, potassium iodide, 2-mercaptoethanol (thioglycol), ascorbic acid, sodium thiosulfate, sodium dithionite, sodium sulfite and salts thereof.

Example 12

[0056] Various alkylphosphonic acid monomethyl esters were dissolved in a high boiling point mineral oil in amounts such that 0.1 M solutions were formed. The solutions were each distilled in accordance with ASTM D-86 and the distillates obtained were analyzed for phosphorus by Inductively Coupled Plasma methodology (ASTM D-4951). The results of these tests are given in Table IX.

TABLE IX

Volatile Phosphorus Formed From Distillation Of Alkylphosphonic Acid Monomethyl Esters In Mineral Oil	
Ester	Phosphorus in Distillate, ppm
octylphosphonic acid monomethyl ester	148
decylphosphonic acid monomethyl ester	38
dodecylphosphonic acid monomethyl ester	12
tetradecylphosphonic acid monomethyl ester	6
hexadecylphosphonic acid monomethyl ester	5
octadecylphosphonic acid monomethyl ester	3

TABLE IX (continued)


Volatile Phosphorus Formed From Distillation Of Alkylphosphonic Acid Monomethyl Esters In Mineral Oil	
Ester	Phosphorus in Distillate, ppm
C ₂₀₋₂₄ alkanephosphonic acid monomethyl ester	<1

[0057] Table IX shows a clear trend in which the volatile phosphorus produced by the alkylphosphonic acid monomethyl esters is a function of molecular weight. Tetradecylphosphonic acid monomethyl ester shows a 96% reduction in volatile phosphorus over the octylphosphonic acid monomethyl ester. The fact that the C₂₀₋₂₄ alkylphosphonic acid monomethyl ester had no detectable volatile phosphorus shows that decomposition due to hydrolysis has been eliminated under the test conditions.

[0058] From Table IX it is apparent the alkylphosphonic acid monomethyl esters of C14 (tetradecyl) or higher are preferred to minimize volatile phosphorus. Of these, tetradecylphosphonic acid monomethyl ester is most preferred to reduce volatile phosphorus while retaining good solubility properties at room temperature.

Claims


1. A hydrocarbon liquid gelling agent comprising a ferric iron or aluminium polyvalent metal salt of a phosphonic acid ester, said phosphonic acid ester having the formula



wherein R is an alkyl group having from about 8 to about 24 carbon atoms and R' is an alkyl group having from about 1 to about 4 carbon atoms.

2. A gelling agent according to claim 1, wherein R is an alkyl group having from 14 to 24 carbon atoms, and/or R' is an alkyl group having 1 or 2 carbon atoms.
3. A gelled liquid hydrocarbon fluid composition comprising a hydrocarbon liquid; a gelling agent as claimed in claim 1 or 2; water; and a delayed gel breaker present in an amount effective to break the gel formed by said gelling agent and said hydrocarbon liquid.
4. The composition according to claim 3, wherein said hydrocarbon liquid is an olefin, kerosene, diesel oil, gas oil, fuel oil, petroleum distillate or crude oil.
5. A composition according to claim 3 or 4, wherein said ferric iron salt is selected from ferric sulphate and ferric chloride, and said aluminium compound is selected from aluminium chloride, aluminium sulphate and aluminium isopropoxide.
6. A composition according to claim 3, 4 or 5, wherein said ferric iron or aluminium polyvalent metal salt of said phosphonic acid ester is present in said hydrocarbon liquid in an amount of from 0.1% to 2.5% by weight of said hydrocarbon liquid.
7. A composition according to claim 3, 4, 5 or 6, wherein said delayed gel breaker is an alkaline earth metal oxide, an alkali metal carbonate, an alkali metal bicarbonate, an alkali metal acetate, an alkali metal hydroxide, an amine or a weak acid which is slowly water soluble, or is encapsulated with a slowly water soluble or other similar encapsulating material.

8. A composition according to claim 7, wherein said delayed gel breaker is slowly water soluble, hard burned magnesium oxide.
9. A composition according to any of claims 3 to 6, wherein said delayed gel breaker is a reducing agent that reduces ferric iron to ferrous iron, preferably encapsulated with a slowly water soluble or other similar encapsulating material.
10. A composition according to claim 9, wherein said reducing agent is stannous chloride, thioglycolic acid or a salt thereof, hydrazine sulphate, sodium diethyldithiocarbamate, sodium dimethyldithiocarbamate, sodium hypophosphite, hydroxylamine hydrochloride, thioglycol, ascorbic acid or a salt thereof, sodium thiosulfate, or sodium sulfite.
11. A composition according to any of claims 3 to 10, wherein said gel breaker is present in said gelled hydrocarbon liquid in an amount of from 0.01% to 3% by weight of said hydrocarbon liquid.
12. A gelled liquid hydrocarbon fracturing fluid which comprises a gelled liquid hydrocarbon fluid as claimed in any of claims 3 to 11, and a proppant material.
13. A method of fracturing a subterranean formation comprising contacting said subterranean formation with a gelled hydrocarbon fracturing fluid as claimed in claim 12, under conditions effective to create at least one fracture in said subterranean formation.
14. A method of preparing a gelled liquid hydrocarbon fluid as claimed in claim 3, comprising adding a phosphonic acid ester to a hydrocarbon liquid, the phosphonic acid ester having the formula



wherein R is an alkyl group having from 8 to 24 carbon atoms and R' is an alkyl group having from 1 to 4 carbon atoms, at least a stoichiometric amount of a polyvalent metal source selected from ferric iron salts and aluminium compounds which reacts with said phosphonic acid ester to form a ferric iron or aluminium polyvalent metal salt thereof, water and an amount of a delayed gel breaker effective to break said gelled hydrocarbon fracturing fluid.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 25 1171

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y,D	US 4 622 155 A (HARRIS LAWRENCE E ET AL) 11 November 1986 (1986-11-11) * the whole document *	1,2	E21B43/26
Y	US 5 529 125 A (DI LULLO ARIAS GINO F ET AL) 25 June 1996 (1996-06-25) * column 2, line 64 - column 3, line 16 * * column 11, line 16 - line 18 * * column 14, line 23 - line 35 *	1,2	
A	US 5 846 915 A (SMITH KEVIN W ET AL) 8 December 1998 (1998-12-08) * column 3, line 21 - column 4, line 19; claim 1 *	1-14	
A	EP 0 919 695 A (FRACMASTER LTD) 2 June 1999 (1999-06-02) * paragraphs '0005!', '0010!', '0014!' *	1	
A	DE 198 56 729 A (COGNIS DEUTSCHLAND GMBH) 15 June 2000 (2000-06-15) * the whole document *	1	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	US 5 871 049 A (PARKER MARK A ET AL) 16 February 1999 (1999-02-16) * column 5, line 51 - column 6, line 3 * * column 6, line 53 - column 7, line 3 *	1	E21B
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 3 May 2002	Examiner Giorgini, G
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPC FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 1171

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

03-05-2002

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4622155 A	11-11-1986	NONE	
US 5529125 A	25-06-1996	AT 206800 T	15-10-2001
		AU 703103 B2	18-03-1999
		AU 4685496 A	24-07-1996
		DE 69523176 D1	15-11-2001
		DE 69523176 T2	31-01-2002
		DK 800613 T3	19-11-2001
		EP 0800613 A1	15-10-1997
		NO 973025 A	27-06-1997
		WO 9621084 A1	11-07-1996
US 5846915 A	08-12-1998	CA 2199169 A1	27-04-1997
		EP 0800562 A1	15-10-1997
		NO 970905 A	26-08-1997
		WO 9715638 A1	01-05-1997
		US 5807812 A	15-09-1998
EP 0919695 A	02-06-1999	AU 9410098 A	17-06-1999
		EP 0919695 A2	02-06-1999
		NO 985482 A	26-05-1999
		US 6184184 B1	06-02-2001
DE 19856729 A	15-06-2000	DE 19856729 A1	15-06-2000
		WO 0034412 A1	15-06-2000
		EP 1149139 A1	31-10-2001
		NO 20012851 A	03-07-2001
US 5871049 A	16-02-1999	US 5775425 A	07-07-1998
		US 5787986 A	04-08-1998
		US 5582249 A	10-12-1996
		US 5501274 A	26-03-1996
		BR 9706876 A	29-06-1999
		CA 2217638 A1	19-11-1998
		EP 0879935 A2	25-11-1998
		NO 974556 A	20-11-1998
		US 5960878 A	05-10-1999
		US 5853048 A	29-12-1998
		BR 9706874 A	15-06-1999
		CA 2217627 A1	03-04-1998
		EP 0834644 A2	08-04-1998
		NO 974553 A	06-04-1998
		US 6047772 A	11-04-2000
		US 6209643 B1	03-04-2001
		US 5839510 A	24-11-1998
		US 5833000 A	10-11-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 02 25 1171

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

03-05-2002

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5871049 A	DE	69519017 D1	09-11-2000
	DE	69519017 T2	15-02-2001
	DK	735235 T3	06-11-2000
	EP	0735235 A1	02-10-1996
	NO	953109 A	30-09-1996
<hr/>			

EPO FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)